



*Decorative variant shown

GENERAL SPECIFICATIONS

ANGLE TO VIEW:

HEIGHT: 2.4m

POST SECTION: 100mm x 55mm RSJ

HORIZONTALS: 60mm x 10mm flat bar rails fixed to posts with M10 cup sq bolts and permacones.

POST CENTRES: 2750mm

INFILL: 25mm square bar verticals welded to rails at 154mm centres, tops of vertical machine pointed to 45°.

FINISH: Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

OPTIONS: Other heights/specifications available on request.

KEY FEATURES: A strong and durable system blending aesthetics with a practical physical deterrent to intruders. Can be colour coated to match corporate colours.

*All dimensions represent nominal values.

CONVEX TOPS:

HEIGHT: 2.4m

POST SECTION: Wall Brackets

HORIZONTALS: 60mm x 10mm flat bar rails fixed to wall brackets with M10 cup sq bolts and permacones.

POST CENTRES: 2500mm

INFILL: 25mm square bar verticals welded to rails at 120mm centres.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, either with manual or automated control.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- ▶ NK CAM railings
- ▶ NK Blackstaff Railings
- ▶ NK Traditional Railings
- ▶ NK Pedestrian Guard Rail

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019