



NK PARKS & PLAYGROUNDS

GENERAL SPECIFICATIONS

HEIGHT: 0.9m, 1.0m, 1.1m, 1.2m.

POST DETAIL: 40 - 50mm SHS with PVC cap, 4 times cleated to receive panels, post centres 2828 - 2838mm.

PANEL DETAIL: 40 x 10mm flat bar top and bottom horizontal rails with 12mm diameter verticals at 112mm centers forming bowtop.

OPTIONS: A range of matching gates are available on request.

FINISH: Galvanised to BS EN 1461:2009 and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

INTENDED USE: Attractive and robust railing system suitable for parks, play areas and housing developments as decorative low level perimeter.

*All dimensions represent nominal values.

RELATED PRODUCTS



SWINGING GATES: Single and Double Leaf Swinging Gates are available in a range of standard widths to suit your individual requirements, either with manual or self-closing devices.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- ▶ NK CAM Railings
- ▶ NK Industrial Railings
- ▶ NK Traditional Railings
- ▶ NK Bespoke Railings
- ▶ NK Pedestrian Guard Rail

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019